

PCE Material Safety Data Sheet

Manufacturer's Name:	Martin Asphalt Company			Date: January 15, 2014				
Telephone Number: 800-662-0987			Addre	ess: 300 Christy Place				
				South Houston, TX 77587				
For Emergency Assistance Call: (713) 941-4410								
NFPA HAZARD IDENTIFICATION		DEGREE OF HAZARD		HAZARD RATINGS				
		HEALTH: 0 FIRE: 0		0= LEAST 1= SLIGHT				
		REACTIVITY: 0			2= MODERATE			
				3= HIGH				
				4= EXTREME				
	SECTIO	N 1 - CO	MPONE	NT DATA				
PRODUCT NAME:	PCE/LVOC-1							
Common Name	BLENDED PETROLE	UM HYDROCARBON						
CHEMICAL NAME	BLENDED PETROLEUM HYDROCARBON							
SECTION 2 - PHYSICAL DATA								
C.A.S. NUMBER:			MIXTURE (SEE DATA BELOW)					
BOILING POINT (°F):		212						
SPECIFIC GRAVITY (H20=1):		0.93						
MELTING POINT (°F):		NA						
VAPOR PRESSURE:		17.535 (GAUGE)						
PERCENT VOLATILE:		0						
VAPOR DENSITY (AIR=1):		NA						
EVAPORATIVE RATE (EE=1):		NA						
SOLUBILITY IN WATER:		SOLUBLE						
APPEARANCE AND ODOR:		LIGHT BROWN LIQUID, FAINT PETROLEUM ODOR						
COMPONENT NAME/ CAS NO.		% MIN	% MAX	EXPOSURE LIMITS		UNITS		
HEAVY PARAFFINIC DISTILLATE SOLVENT		50	70	OSHA PEL (OIL MIST)		5 mg/m3		
EXTRACT (HPDSE)/64742-04-7				(OIL MIST)		0.2mg/m3		
EMULSIFIER/ LISTED IN TSC	Â	0	10	ORAL LD50 (RATS) <pre></pre>		<19g/kg		
SECTION 3 - FIRE & EXPLOSION DATA								
FLASH POINT (^O F) & METHO	D:	HPDSE: 4	410 / C.C).C.				
FLAMMABILITY LIMITS:		Lower: Na Upper: Na						
AUTO IGNITION TEMPERATURE (°F):		UNKNOWN						
EXTINGUISHING MEDIA	USE DRY CHEMICAL	EMICAL, FOAM OR CARBON DIOXIDE.						
SPECIAL FIRE FIGHTING	L FIRE FIGHTING WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS EXPOSED TO DURES HEAT OR FLAME. CAUTION SHOULD BE EXERCISED WHEN USING WATER OR FOAM							
PROCEDURES								
	AS FROTHING MAY OCCUR, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING LIQUID.							
UNUSUAL FIRE AND DENSE SMOKE MAY BE GENERATED WHILE BURNING. CARBON MONOXIDE, CARBON								
EXPLOSIVE CONDITIONS								

*NA=NOT APPLICABLE **ND=NOT DETERMINED



SECTION 4 - REACTIVITY DATA					
STABILITY: STABLE		STABLE			
CONDITIONS TO AVOID:		NONE			
HAZARDOUS POLYMERIZATION:		WILL NOT OCCUR			
INCOMPATIBILITY MATERIALS TO AVOID:		MAY REACT WITH STRONG OXIDIZING AGENTS			
HAZARDOUS DECOMPOSITION PRODUCTS:		NONE			
	SECTION 5 - HEALTH HAZARD DATA				
SKIN CONTACT:	AVOID SKIN CONTACT, THIS PRODUCT MAY CAUSE SLIGHT SKIN IRRITATION UPON DIRECT CONTACT; BASED ON TESTING OF SIMILAR PRODUCTS AND/OR COMPONENTS. PROLONGED OR REPEATED CONTACT MAY RESULT IN CONTACT DERMATITIS WHICH MAY MAKE THE SKIN MORE SUSCEPTIBLE TO OTHER IRRITANTS, SENSITIZERS AND DISEASE. PROLONGED OR REPEATED CONTACT MAY RESULT IN OIL ACNE WHICH IS CHARACTERIZED BY BLACKHEADS WITH POSSIBLE SECONDARY INFECTION. CONSTITUENTS OF THIS PRODUCT HAVE BEEN ASSOCIATED WITH PHOTOSENSITIVITY AN ABNORMAL SENSITIVITY OF SKIN TO SUNLIGHT. SEE DATA HEALTH BELOW				
EYE CONTACT:	THIS PRODUCT IS RELATIVELY NON-IRRITATING TO THE EYES UPON DIRECT CONTACT BASED ON TESTING OF SIMILAR PRODUCTS AND/OR COMPONENTS.				
INHALATION:	THIS PRODUCT HAS A LOW VAPOR PRESSURE AND IS NOT EXPECTED TO PRESENT AN INHALATION HAZARD AT AMBIENT CONDITION. CAUTION SHOULD BE TAKEN TO PREVENT AEROSOLIZATION OR MISTING OF THIS PRODUCT. THE PERMISSIBLE EXPOSURE LIMIT (PEL) AND THRESHOLD LIMIT VALUE (TLV) FOR THIS PRODUCT AS OIL MIST IS 5 mg/m3 APPEAR TO BE WITHOUT SIGNIFICANT HEALTH RISK. THE SHORT-TERM EXPOSURE LIMIT FOR THIS PRODUCT AS AN OIL MIST IS 10 mg/m3.				
INGESTION	DO NOT INGEST. THIS PRODUCT IS RELATIVELY NON- TOXIC BY INGESTION. THIS PRODUCT HAS LAXATIVE PROPERTIES AND MAY RESULT IN ABDOMINAL CRAMPS AND DIARRHEA. SEE HEALTH DATA BELOW.				
HEALTH DATA	ON RARE OCCASIONS, PROLONGED AND REPEATED EXPOSURE TO OIL MIST POSES A RISK OF PULMONARY DISEASE SUCH AS CHRONIC LUNG INFLAMMATION. THIS CONDITION IS USUALLY ASYMPTOMATIC AS A RESULT OF REPEATED SMALL ASPIRATIONS. SHORTNESS OF BREATH AND COUGH ARE THE MOST COMMON SYMPTOMS. THE PETROLEUM OIL USED FOR THIS PRODUCT IS CLASSIFIED AS CARCINOGENIC BY THE INTERNATIONAL AGENCY FOR RESEARCH OF CANCER. TO MINIMIZE EXPOSURE, DO NOT SUBJECT EMULSION TO TEMPERATURES ABOVE 212°F. TEMPERATURES IN THIS RANGE VOLATILIZE THE EMULSION.				
SECTION 6 - EMERGENCY AND FIRST AID PROCEDURES					
EYE CONTACT		E AMOUNTS OF WATER AND CONTINUE FLUSHING RIAL IS HOT, TREAT FOR THERMAL BURNS AND TAKE			
SKIN CONTACT	REMOVE CONTAMINATED CLOTHING. WASH CONTAMINATED AREA THOROUGHLY WITH SOAP AND WATER. IF REDNESS OR IRRITATION OCCURS, SEEK MEDICAL ATTENTION. IF MATERIAL IS HOT, SUBMERGE INJURED AREA IN COLD WATER. IF VICTIM IS SEVERLEY BURNED, REMOVE TO A HOSPITAL IMMEDIATELY.				
INHALATION	THIS MATERIAL HAS A LOW VAPOR PRESSURE AND IS NOT EXPECTED TO PRESENT AN INHALATION EXPOSURE AT AMBIENT CONDITIONS.				
INGESTION	DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.				

*NA=NOT APPLICABLE **ND=NOT DETERMINED



	ASPHALT COMPANY				
SECTION 7 - PERSONAL HEALTH PROTECTION INFORMATION					
EYE PROTECTION	EYE PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. IF MATERIAL IS HANDLED SUCH THAT IT COULD BE SPLASHED INTO EYES, WEAR PLASTIC FACE SHIELD OR SPLASH-PROOF SAFETY GOGGLES.				
SKIN PROTECTION	NO SKIN PROTECTION IS REQUIRED FOR SINGLE SHORT DURATION EXPOSURES, USE IMPERVIOUS CLOTHING (BOOTS, GLOVES, APRONS, ETC.) OVER PARTS OF THE BODY SUBJECT TO EXPOSURE. IF HANDLING HOT MATERIAL, USE INSULATED PROTECTIVE CLOTHING (BOOTS, GLOVES, APRONS, ETC.) LAUNDER SOILED CLOTHES. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES INCLUDING SHOES, WHICH CANNOT BE DECONTAMINATED.				
RESPIRATORY PROTECTION	RESPIRATORY PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. IF VAPOR OR MIST IS GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, USE AN ORGANIC VAPOR RESPIRATOR WITH A DUST AND MIST FILTER. ALL RESPIRATORS MUST BE NIOSH CERTIFIED. DO NOT USE COMPRESSED OXYGEN IN HYDROCARBON ATMOSPHERES.				
VENTILATION	IF VAPOR OR MIST IS GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, ADEQUATE VENTILATION IN ACCORDANCE WITH GOOD ENGINEERING PRACTICE MUST BE PROVIDED TO MAINTAIN CONCENTRATIONS BELOW THE SPECIFIED EXPOSURE OR FLAMMABLE LIMITS.				
OTHER	CONSUMPTION OF FOOD AND BEVERAGES SHOULD BE AVOIDED IN WORK AREAS WHERE HYDROCARBONS ARE PRESENT. ALWAYS WASH HANDS AND FACE WITH SOAP AND WATER BEFORE EATING, DRINKING, OR SMOKING.				
SECTION 8 - SPILL, LEAK & DISPOSAL PROCEDURES					
STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED	CONSULT HEALTH HAZARD DATA IN SECTION 5, PERSONAL HEALTH PROTECTION INFORMATION IN SECTION 7, FIRE & EXPLOSION DATA IN SECTION 3, AND REACTIVITY DATA IN SECTION 4. NOTIFY APPROPRIATE AUTHORITIES OF SPILL. CONTAIN SPILL IMMEDIATELY. DO NOT ALLOW SPILL TO ENTER SEWERS OR WATERCOURSES. REMOVE ALL SOURCES OF IGNITION. ABSORB WITH APPROPRIATE INERT MATERIAL SUCH AS SAND, CLAY, ETC. LARGE SPILLS MAY BE PICKED UP USING VACUUM PUMPS, SHOVELS, BUCKETS OR OTHER MEANS AND PLACED IN DRUMS OR OTHER SUITABLE CONTAINERS.				
WASTE DISPOSAL METHOD	ALL DISPOSALS MUST COMPLY WITH FEDERAL, STATE, AND LOCAL REGULATIONS. THE MATERIAL, IF SPILLED OR DISCARDED, MAY BE A REGULATED WASTE. REFER TO STATE AND LOCAL REGULATIONS. CAUTION! IF REGULATED SOLVENTS ARE USED TO CLEAN UP SPILLED MATERIAL, THE RESULTING WASTE MIXTURE MAY BE REGULATED. DEPARTMENT OF TRANSPORTATION (DOT) REGULATIONS MAY APPLY FOR TRANSPORTING THIS MATERIAL WHEN SPILLED. WASTE MATERIAL MAY BE LANDFILLED OR INCINERATED AT AN APPROVED FACILITY. MATERIALS SHOULD BE RECYCLED IF POSSIBLE.				
SECTION 9 - SPECIAL PRECAUTIONS/ADDITIONAL INFORMATION					
HANDLING AND STORAGE REQUIREMENTS	DO NOT TRANSFER TO UNMARKED CONTAINERS. STORE IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN FLAME, OR OXIDIZING MATERIALS. THIS PRODUCT IS NOT CLASSIFIED AS HAZARDOUS UNDER DOT REGULATIONS. FIRE EXTINGUISHERS SHOULD BE KEPT READILY AVAILABLE. SEE NFPA 30 AND OSHA 1910.106 FLAMMABLE AND COMBUSTIBLE LIQUIDS.				
ADDITIONAL INFORMATION	THIS PRODUCT IS NOT KNOWN TO CONTAIN ANY SARA TITLE III, SECTION 313 REPORTABLE CHEMICALS, AT OR GREATER THAN 1.0% (0.1% FOR CARCINOGENS) A COMPONENT OF THIS PRODUCT IS ON THE TOXIC SUBSTANCES CONTROL ACT (TSCA) INVENTORY.				

The information contained herein is based on the data available to us and is believed to be correct. However, Martin Asphalt Company makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. This information and product is furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of use thereof.

*NA=NOT APPLICABLE **ND=NOT DETERMINED