

EVERYTHING ASPHALT

#800 Everlock Adhesive

“Your Source for Everything Asphalt”



Product Description

Everlock 800 is a hot poured adhesive for wood flooring that firmly and permanently bonds screeds to slabs. For more than 40 years, wood flooring professionals have depended on Everlock 800 because of its superior adhesion, reliability and ease of application.

Typical Physical Properties

Everlock 800 is a blend of selected asphaltic materials.

<i>Consistency</i>	Highly Viscous Liquid
<i>Flash point, (ASTM D-3143)</i>	140°F/60°C
<i>Weight per Gallon</i>	8.2 – 8.5 lbs
<i>Weight per Liter</i>	0.98 – 1.20 kg
<i>Chemical resistance to mild acids & alkali</i>	Good

Application

The surfaces should be clean and dry. Everlock 800 should be heated in an open & well-ventilated area until fluid (approx. 325-360°F/163 – 177°C). Hot adhesive should be poured onto the slab at a rate of one gallon per sq. ft. (0.5 m² per liter) of surface area. Everlock 800 should be spread with a wooden spoon, notched squeegee with teeth approx. 1" (25.4mm) wide and ¼" (6.35mm) apart. Screeds should be clean, straight and dry from a two-by-four 18-30" (457-762mm) long. Screeds should be laid at a 90° angle to the finished floor 20 minutes after applying the adhesive. Screeds should be parallel to each other and 4" (102mm) apart. Finished wood flooring can be nailed to the screeds immediately after the screeds are placed on the adhesive. Minor adjustments to the location of the screeds can be made prior to nailing.

Note: It is recommended but not required that surface be primed with Everlock 204 Primer for concrete prior to application of Everlock 800.

Coverage

Typical coverage per gallon is 20 sq. ft. (0.5m² per liter). Everlock 800 is ready to use after heating. It should not be thinned.

Storage and Handling

Everlock 800 should be stored in a dry place protected from the elements. The product should be used in a well-ventilated area.

Clean-up

Asphalt stains can be removed with non-hazardous, bio-degradable cleaners. Waterless hand cleaners should be used on skin, following the cleaner manufacturer's instructions carefully.

Advantages

- Permanent bond
- Excellent waterproofing qualities
- Protects against vapor intrusion
- Absorbs noise better for soundproofing
- Flexible movement without debonding
- Easy installation
- Proven performance
- Non-chlorinated solvents

	Packaging	
<i>Size of Container</i>	5 gallon pail	55 gallon drum
<i>Approx. Weight/Container</i>	45 lbs (20.5kg)	489 lbs (222 kg)
<i>Units/Pallet</i>	36 units/pallet	4 drums/pallet

Martin Asphalt Company
Three Riverway, Suite 1250
Houston, TX 77056
www.martinasphalt.com
713-350-5350